

# WISA®-Parquet Veneer

WISA-Parquet Veneer is a fit-to-purpose component as base veneer for three layer parquets. WISA-Parquet Veneers are ready for customer's manufacturing process immediately after received, since veneer moisture level has been balanced in advance.

## Product

Veneer made of spruce (Picea Abies)

## Quality

Standard parquet quality

Sound knots allowed

Open knot diameter max. 40 mm

Split length max. 500 mm and width max. 10 mm

## Thickness

2.0 mm thick veneer as standard.

## Veneer sizes

Veneers are cut according to customer specifications. Lengths are possible up to 2540 mm and widths up to 1350 mm.

## Moisture Controlled Veneers

Customer's manufacturing process becomes more efficient as the veneers are ready for use right after received. Moisture balance in veneers is achieved by state of art moisture balance technology. The moisture is continuously monitored by a computer aid control system and every veneer sheet is balanced individually.



For PEFC™ products, visit [www.pefc.org](http://www.pefc.org)



The mark of responsible forestry  
For FSC® products, visit [www.fsc.org](http://www.fsc.org)





## Tolerances

	Standard Range	Tolerance
Thickness (mm)	2	+0.2/- 0.1
Length (mm)	1200 – 2540	+5/- 0
Width (mm)	150 – 799	+5/- 0
	800 – 1350	+10/- 0
<b>Moisture content (%)</b>		
Standard	2 – 8	±2 % unit
Moisture controlled	from 4 to 8	±1 % unit

## Veneer properties

Our veneers go through constant quality securing process in all stages of the production. Dimensions, moisture and quality are measured several times to secure the right grade. Thin but strong veneer balances the three layer parquet construction and keeps it straight.

Our production aims to fulfil customer needs and constantly develops products and services in tight co-operation with our sales and R&D department.

## Packaging and storage instructions

Veneer pallets are sealed with plastic foil to secure the right moisture and quality to our customers. Veneer pallet is protected with hermetic packaging from all six faces. Veneers should be stored flat in a dry covered place.

## Environment

WISA products are manufactured in Europe according to the strictest sustainability principles. By choosing WISA, our customers can have the confidence that their plywood and veneer come only from legal sources and conform to all relevant standards and regulations, including the European Union Timber Regulation (EUTR).

UPM leads the integration of bio and forest industries into a sustainable future characterised by innovation, responsibility and resource efficiency.

## Additional information

Wood being a living material, every panel is unique. Thus a photograph or a sample piece cannot represent all the panels, as regards colours, shades, graining, knots etc.

For further information of installation, maintenance, disposal, environmental matters etc. please see [www.wisaplywood.com](http://www.wisaplywood.com) or contact your supplier or UPM.

