

## DECLARATION OF PERFORMANCE, UPM PLYWOOD

No. **UPM015CPR**

1. Unique identification code of the product-type:  
Non-structural birch plywood, uncoated or coated, 4–50 mm
2. Intended uses:  
For internal use as a non-structural component in dry conditions, EN 636-1  
For protected external use as a non-structural component in humid conditions, EN 636-2
3. Manufacturer:  
WISA®  
UPM Plywood Oy  
P.O. Box 203  
FI-15141 Lahti, Finland  
www.wisaplywood.com
5. System of AVCP:  
AVCP system 4
7. Declared performance:

Essential characteristics	Performance	Harmonised standard
Point load strength and stiffness	NPD	EN 13986:2004+A1:2015
Racking resistance	NPD	
Impact resistance	NPD	
Water vapour permeability $\mu$	Wet 90, dry 220 (uncoated)	
	Mean density 680 kg/m <sup>3</sup>	
Release of formaldehyde	E1	
Content of pentachlorophenol (PCP)	≤ 5 ppm	
Airborne sound insulation	NPD	
Sound absorption $\alpha$	0,10/0,30	
Thermal conductivity $\lambda$	0,17 W/mK	
Embedment strength	NPD	
Air permeability	NPD	
Bonding quality (acc. to EN 314-2)	Class 3	
Biological durability	Use class 2	

Reaction to fire			
End use condition <sup>(6)</sup>	Minimum thickness (mm)	Class <sup>(7)</sup> (excluding floorings)	Class <sup>(8)</sup> (floorings)
Without an air gap behind the wood-based panel <sup>(1), (2), (5)</sup>	9	D-s2, d0	D <sub>fl</sub> -s1
With a closed or an open air gap not more than 22 mm behind the wood-based panel <sup>(3), (5)</sup>	9	D-s2, d2	-
With a closed air gap behind the wood-based panel <sup>(4), (5)</sup>	15	D-s2, d1	D <sub>fl</sub> -s1
With an open air gap behind the wood-based panel <sup>(4), (5)</sup>	18	D-s2, d0	D <sub>fl</sub> -s1
Any <sup>(5)</sup>	3	E	E <sub>fl</sub>

<sup>(1)</sup> Mounted without an air gap directly against class A1 or A2-s1, d0 products with minimum density 10kg/m<sup>3</sup> or at least class D-s2, d2.

<sup>(2)</sup> A substrate of cellulose insulation material of at least class E may be included if mounted directly against the wood-based panel, but not for floorings.

<sup>(3)</sup> Mounted with an air gap behind. The reverse face of the cavity shall be at least class A2-s1, d0 products with minimum density 10 kg/m<sup>3</sup>.

<sup>(4)</sup> Mounted with an air gap behind. The reverse face of the cavity shall be at least class D-s2, d2 products with minimum density 400 kg/m<sup>3</sup>.

<sup>(5)</sup> Veneered, phenol- and melamine-faced panels are included for class excl. floorings.

<sup>(6)</sup> A vapour barrier with a thickness up to 0,4 mm and a mass up to 200 g/m<sup>2</sup> can be mounted in between the wood-based panel and a substrate if there are no air gaps in between.

<sup>(7)</sup> Class as provided for in Table 1 of the Annex to Decision 2000/147/EC.

<sup>(8)</sup> Class as provided for in Table 2 of the Annex to Decision 2000/147/EC.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Lahti, Finland, November 5th, 2018



Sirku Salmikuukka, Product Manager  
UPM Plywood